

# BEYOND POPULAR SCIENCE



DAVID H. SILVER



## BEYOND POPULAR SCIENCE

David H. Silver

<https://www.openbookpublishers.com>

© 2026 David H. Silver



This work is licensed under the Creative Commons Attribution-NonCommercial 4.0 International (CC BY-NC 4.0). This license allows you to share, copy, distribute and transmit the text; to adapt the text for non-commercial purposes of the text providing attribution is made to the authors (but not in any way that suggests that they endorse you or your use of the work). Attribution should include the following information:

David H. Silver, *Beyond Popular Science*. Cambridge, UK: Open Book Publishers, 2026,  
<https://doi.org/10.11647/OBP.0526>

Further details about CC BY-NC licenses are available at  
<https://creativecommons.org/licenses/by-nc/4.0/>

Copyright and permissions for the reuse of many of the images included in this publication differ from the above. This information is provided in the captions and in the list of illustrations. Unless otherwise stated, figures are reproduced under the fair dealing principle. Every effort has been made to identify and contact copyright holders and any omission or error will be corrected if notification is made to the publisher.

All external links were active at the time of publication unless otherwise stated and have been archived via the Internet Archive Wayback Machine at  
<https://archive.org/web>

Digital material and resources associated with this volume are available at  
<https://doi.org/10.11647/OBP.0526#resources>

ISBN Paperback:	978-1-80511-877-0
ISBN Hardback:	978-1-80511-878-7
ISBN Digital (PDF):	978-1-80511-879-4
ISBN HTML:	978-1-80511-881-7
ISBN Digital ebook (epub):	978-1-80511-880-0
DOI:	10.11647/OBP.0526

Cover image by Enny Silver and David H. Silver  
Cover design by Jeevanjot Kaur Nagpal

**It Is Just a  
Phase**

**Top (Pixel-Level Edge Detection):**

Each observer inspects a single pixel and flags whether it looks like part of an edge. This approach produces isolated detections without context—assembling a full line requires comparing scattered responses after the fact. It's data-rich but structure-poor: the system sees points, not lines.


**Middle (Line-Level Hough Detection):**

Observers instead scan the whole image through virtual rulers at specific angles and offsets. Each one votes if their ruler aligns with edge evidence. The same number of detectors now deliver global outputs: lines directly. This is the core idea behind the Hough Transform—accumulating evidence in a parameter space where lines become peaks.

**Bottom (Phase Space Riddle):**


Two roads connect cities A and B without crossing. A pair of cars, tied by a rope of length  $< 2R$ , can travel side by side on these roads from A to B. Now consider two circular wagons of radius  $R$ , each centred on its own path—one going A to B, the other B to A. Let  $(x, y)$  track their positions along the two roads, forming a trajectory in the unit square

$I = \{(x, y) : 0 \leq x, y \leq 1\}$ . The cars' path goes from  $(0, 0)$  to  $(1, 1)$ ; the wagons' from  $(1, 0)$  to  $(0, 1)$ . By topology, these curves must intersect. At the intersection, the wagons occupy the same positions as the cars once did, yet their centres are  $< 2R$  apart, and each wagon has radius  $R$ , so a collision is unavoidable. A fact that is difficult to prove directly. (After Konstantinov, in Arnold's *ODEs*.)



# It Is Just a Phase

The Hough transform detects geometric shapes in images by converting the problem from image space to parameter space. Images undergo edge detection to identify significant brightness transitions. Each edge pixel then ‘votes’ for all possible geometric structures that could contain it. For line detection, edge points generate constraints in parameter space through the relation  $b = y_0 - mx_0$ . Points lying on the same line create intersecting lines in parameter space, forming accumulator peaks.



HOUGH TRANSFORM ◦ EDGE DETECTION ◦ PARAMETER SPACE  
VOTING ◦ RHO-THETA PARAMETRISATION ◦ ACCUMULATOR  
ARRAYS ◦ GLOBAL FEATURE DETECTION ◦ LINE FINDING  
ALGORITHM ◦ GRADIENT OPERATORS ◦ CIRCLE  
DETECTION ◦ COMPUTER VISION ◦ DUALITY TRANSFORM

“With four parameters I can fit an elephant,  
and with five I can make him wiggle his trunk.”

— John von Neumann, circa 1953



A curve found in 2010 as shown above.  
The curve can be fitted with four parameters.  
A fifth point can be added to form the elephant's eye  
and allows the trunk to move.  
— Jürgen Mayer, Khaled Khairy, Jonathon Howard, 2010

## It Is Just a Phase

In 1959, Paul V. C. Hough filed a patent—issued in 1962 as U.S. Patent 3,069,654—for a method of identifying complex patterns in visual data by mapping image features into a parameter space. His technique framed detection as finding parameter settings supported by many edge points. The familiar sinusoidal loci in a polar-coordinate domain arise with the normal parameterisation  $(\rho, \theta)$ , which was formalised and popularised subsequently.

Early implementations relied on analogue hardware and optical computing elements. Limitations in memory and processing speed constrained accumulator resolution and the range of detectable geometries. Despite these constraints, the method was adopted in early automation systems for detecting weld lines, highway markings, and parts in mechanical assemblies.

In 1972, Richard Duda and Peter Hart provided the first formal exposition of the method in their landmark paper, reframing it as a discrete voting process over a bounded parameter space and introducing the normal parameterisation  $\rho = x \cos \theta + y \sin \theta$  that treats all orientations uniformly. Their formulation gave the method the name ‘Hough transform’ and connected it to broader principles in statistical decision theory. Subsequent extensions by Ballard and others generalised the idea to arbitrary curves and spatial templates, enabling detection of circles, ellipses, and parabolas.

By the 1980s and 1990s, with advances in digital signal processors and parallel computing, the Hough transform became a foundational tool in industrial vision systems, robotics, and medical image reconstruction. Its structure-preserving mapping from image to parameter space allowed for robust detection even in the presence of occlusion, fragmentation, and noise—a capacity that remains central to modern implementations in lane detection, tomography, and motion analysis.

A digital image is a two-dimensional discrete function  $I(x, y)$  defined over a finite grid of integer coordinates. Each ordered pair  $(x, y)$  refers to a spatial location in the image plane, and the corresponding value  $I(x, y)$  denotes the intensity—or brightness—measured at that position. In standard grayscale images, the intensity values range over a finite interval, typically  $[0, 255]$ , where 0 represents black and 255 represents white. Intermediate values encode proportional levels of grey.

This allows images to be treated as matrices of numerical data. Each row corresponds to a horizontal slice through the image, and each column to a vertical slice. The array format aligns with standard data structures in numerical computing, enabling efficient storage, manipulation, and analysis using linear algebraic tools. More relevantly, this view enables the application of discrete transformations that operate directly on the pixel grid.

The array-based nature of digital images reflects their method of acquisition. Optical sensors—such as charge-coupled devices (CCDs)—sample incoming light (Boyle & Smith, 1970) intensity across a regular lattice of photodetectors. Each photodetector integrates the radiance over a small rectangular region and records the result as a scalar value. This

process discretizes a continuous visual field, replacing smooth spatial variation with a piecewise-constant approximation.

Despite this discretization, many natural images exhibit local continuity. In regions of uniform texture or lighting, adjacent pixels tend to have similar intensity values. This results in spatial smoothness—a statistical tendency that can be exploited by various image processing algorithms. Conversely, abrupt changes in intensity may indicate the presence of physical boundaries, surface discontinuities, or occlusion contours.

The goal of low-level image processing is to extract global geometric elements from the raw intensity field—to identify where transitions occur, how they are oriented, and how they combine to form recognisable configurations. The first step in this process is edge detection: identifying where intensity values change significantly in space.

To extract localised transitions in brightness, digital image processing employs gradient-based methods. These techniques compute spatial derivatives of the intensity function  $I(x, y)$  using discrete convolution kernels. Common approximations include the Sobel, Prewitt, or central (Sobel, 1970) difference operators, which estimate the partial derivatives  $\partial I/\partial x$  and  $\partial I/\partial y$  by combining intensities in a small neighborhood.

The result of this process is a vector field  $G(x, y) = (I_x(x, y), I_y(x, y))$ , where  $I_x$  and  $I_y$  denote the horizontal and vertical gradients respectively. The magnitude of this vector, defined as

$$\|G(x, y)\| = \sqrt{I_x(x, y)^2 + I_y(x, y)^2},$$

quantifies the rate of change in brightness at each pixel. The direction  $\theta(x, y) = \arctan 2(I_y, I_x)$  indicates the orientation of maximal contrast—that is, the direction perpendicular to the local edge.

To reduce the resulting field to a usable form, a fixed threshold is applied to the gradient magnitude. The binary edge map  $E(x, y)$  is defined by

$$E(x, y) = \begin{cases} 1 & \text{if } \|G(x, y)\| > \tau, \\ 0 & \text{otherwise,} \end{cases}$$

where  $\tau$  is a positive scalar threshold. The outcome is a sparse array in which  $E(x, y) = 1$  denotes an edge candidate and 0 otherwise. This thresholding step suppresses minor fluctuations while preserving strong transitions, isolating regions of significant spatial variation.

The resulting edge map retains only local information. Each nonzero pixel marks a point of abrupt contrast but encodes no higher-order structure. It does not indicate whether a given edge continues across neighbouring pixels, nor whether multiple edge points are aligned.

In many visual tasks, the detection of straight lines is the second step after edge detection. Lines may correspond to physical edges in man-made environments—such as walls, roads, or tools—or to object boundaries under specific perspectives. In medical imaging, remote sensing, and industrial inspection, linear features often identify critical diagnostic or structural information.

However, a straight line is not a local construct. Unlike a gradient, which depends only on immediate neighbours, a line is a global configuration—a set of pixels that, despite spatial separation, conform to a shared geometric constraint. In the discrete setting, this constraint must be inferred from partial and often noisy evidence. The edge map contains a large number of isolated pixels, many of which are spurious. Determining which subsets form lines requires aggregating across potentially distant points.

One naïve approach is to enumerate all pairs of edge pixels and test whether a third or fourth point lies along the same line. Given  $n$  detected edge points, there are  $\binom{n}{2}$  possible pairs, and each pair defines a candidate line. For each such line, one must then check whether additional points fall sufficiently close to it, accounting for quantization and discretization artefacts. The combinatorial burden of this process grows quadratically in the number of edge pixels and becomes intractable at practical image resolutions.

The challenge is further exacerbated by noise and occlusion. Genuine lines may be broken into disconnected segments, and false positives may arise from texture or illumination variations. Any method that seeks to identify lines must accommodate partial evidence and operate under pixel-level uncertainty. The core problem is not to test a single hypothesis, but to efficiently search a vast and noisy hypothesis space for a small number of consistent patterns. To detect lines in a binary edge map, one may adopt a parametric formulation of straight lines. In Cartesian coordinates, the general equation for a line is  $y = mx + b$ , where  $m$  is the slope and  $b$  the vertical intercept. The goal is to identify parameter pairs  $(m, b)$  that describe lines passing through multiple edge pixels.

Each edge pixel  $(x_0, y_0)$  imposes a constraint on the set of valid  $(m, b)$  values. Specifically, if a line passes through  $(x_0, y_0)$ , then its parameters must satisfy

$$y_0 = mx_0 + b, \quad \text{or equivalently,} \quad b = y_0 - mx_0.$$

This relation defines a one-dimensional locus in the  $(m, b)$  parameter space: the set of all lines that intersect  $(x_0, y_0)$ . For fixed  $x_0$  and  $y_0$ , this is a straight line in parameter space—each pixel generates such a line of possible  $(m, b)$  values.

To implement this idea computationally, the  $(m, b)$  space is discretized into a finite grid. A two-dimensional accumulator array is initialised, with each cell corresponding to a quantized pair of slope and intercept values. For each edge pixel, the algorithm evaluates the above relation at discrete samples of  $m$  and computes the corresponding  $b$  values. Each resulting  $(m_i, b_i)$  pair increments the count in its associated cell of the accumulator.

After processing all edge pixels, the accumulator stores the number of pixels consistent with each candidate line. Peaks in this array—cells with significantly elevated counts—represent line parameters that are supported by many pixels. These peaks are interpreted as strong linear features in the original image.

While this method organises the problem effectively, it remains computationally intensive. Each edge pixel must evaluate the constraint over all discretized slope values, resulting in a cost proportional to the product of the number of edge pixels and the number of slope samples. Moreover, the parameterization becomes unstable for nearly vertical lines, where  $m$  diverges. These limitations motivate the adoption of alternative representations, but the

core insight remains: transform each pixel into a family of candidate lines, and identify agreement via intersection in parameter space.

The Hough transform discretizes the  $(m, b)$  space into a finite grid. For each edge pixel, it iterates over a predefined set of slope values  $m_i$  and computes  $b_i = y - m_i x$ . A two-dimensional accumulator array stores how many pixels vote for each parameter pair  $(m_i, b_i)$ . After all edge pixels have contributed, cells in the accumulator with high vote counts correspond to lines that are strongly supported by the data.

This formulation avoids the combinatorial explosion of testing all pixel pairs. Each pixel acts independently, voting for a family of possible lines. Lines with high support appear as peaks in the accumulator, which can be located efficiently using standard search techniques.

In practice, this classical parameterization has limitations near vertical lines, where the slope  $m$  becomes unbounded. A more robust formulation employs the normal parameterization  $\rho = x \cos \theta + y \sin \theta$ , which describes lines using distance and orientation. This variant ensures uniform treatment of all orientations, but the essential idea remains: transform alignment in image space into intersection in parameter space, and use voting to identify consistent structures.

The strength of the Hough transform lies in its ability to transform the problem from image space to parameter space. Once the core mechanism is established—each edge pixel voting for the set of parameters consistent with its location—the method generalises seamlessly to more complex shapes.

For example, consider the problem of detecting circles. A circle in the plane is defined by the equation  $(x - a)^2 + (y - b)^2 = r^2$ , where  $(a, b)$  denotes the centre and  $r$  the radius. Each edge pixel  $(x_0, y_0)$  must satisfy this relation for some triplet  $(a, b, r)$ . If the radius is fixed, then every such pixel defines a circular locus of possible centres—that is, it contributes votes to all  $(a, b)$  such that  $(x_0 - a)^2 + (y_0 - b)^2 = r^2$ . Allowing  $r$  to vary introduces a third dimension: the accumulator now becomes a 3D volume over  $(a, b, r)$ .

This generalises further. Any shape that admits an algebraic parameterization can be detected in the same way. For instance, **ellipses** require five parameters (centre coordinates, major and minor axis lengths, and orientation), while **parabolas** can be parameterized by vertex location and opening direction. Even **arbitrary curves** described by parametric equations or algebraic forms can be handled, provided the number of parameters is finite and reasonably small.

In each case, the edge pixel votes for a hypersurface in the corresponding parameter space. The transform aggregates these votes, and high-density regions in the accumulator indicate the presence of shapes that are strongly supported by the edge data.

The cost of generality is dimensional: for a shape defined by  $k$  parameters, the accumulator array lives in  $\mathbb{R}^k$ . Memory and computation scale exponentially with  $k$ , limiting the practical complexity of detectable shapes. Nevertheless, for many applications—especially where the shape class is known and low-dimensional—the Hough transform remains a tractable and robust detection mechanism.

### Visual Demonstration of Hough Transform




Figure by author. The Hough transform converts lines in image space to points in parameter space (angle, distance). Parallel lines (red) create peaks at the same angle. Lines from a common point (green) create an arc pattern. Even with noise, a line (blue) creates a strong peak in Hough space.

## Radon, Hough, and the Geometry of Detection

### Continuous vs Discrete Detection

Detecting a geometric structure in an image means finding parameters  $p$  for which the curve or surface  $C(x; p) = 0$  is present in the intensity field  $I(x)$ . The Radon and Hough transforms implement this same idea in two complementary ways: one performs a continuous *read-out* along shapes, the other a discrete *write-in* from feature points.

### Transform Duality: Reading vs Writing

Let  $I(x)$  be a spatial image and  $p \in P$  a parameter vector. The Radon transform is the integral projection:

$$R(p) = \int_{\mathbb{R}^n} I(x) \delta(C(x; p)) dx.$$

Here each parameter  $p$  queries all  $x$  satisfying  $C(x; p) = 0$  and accumulates their intensity. In contrast, the Hough transform iterates over image locations: for each  $x_0$  where  $I(x_0) \neq 0$ , it computes all  $p$  with  $C(x_0; p) = 0$  and increments  $H(p)$ .

Let  $\mathcal{C}_p = \{x \in \mathbb{R}^n \mid C(x; p) = 0\}$  denote the locus of points on shape  $p$ , and  $\mathcal{M}_x = \{p \in P \mid C(x; p) = 0\}$  the set of shapes passing through point  $x$ . Then:

$$R(p) = \int_{\mathcal{C}_p} I(x) d\mu(x),$$

(Radon: continuous read-out)

$$H(p) = \sum_{x \in \text{supp}(I)} \mathbf{1}_{\mathcal{M}_x}(p),$$

(Hough: discrete write-in).

Radon computes an inner product between  $I(x)$  and a template restricted to  $\mathcal{C}_p$ , while Hough builds up a histogram in parameter space whose peaks indicate well-supported shapes.

### Unified Operator View

Both transforms can be expressed as linear operators with a kernel  $C(p, x)$ :

$$(\mathcal{L}_C I)(p) = \int_{\mathbb{R}^n} C(p, x) I(x) dx.$$

Choosing  $C(p, x) = \delta(C(x; p))$  recovers Radon-type projections. Replacing the integral by a sum over discrete feature points and incrementing an accumulator at each  $p$  with  $C(x; p) = 0$  yields Hough-type transforms.

If  $C(p, x)$  is shift-invariant, i.e.,  $C(p, x) = K(x - \phi(p))$ , the operator reduces to convolution with a shifted template. This links Radon/Hough methods to classical matched filtering and Fourier-analytic descriptors.

### Intersections in Parameter Space

Every edge point  $x$  defines a manifold  $\mathcal{M}_x \subset P$ . True structures correspond to parameters  $p^*$  where multiple such manifolds intersect, producing sharp peaks in  $H(p)$ . In this view, detection is about the geometry of intersections: coherent data produce persistent intersections that survive noise and discretization, whereas random or spurious features yield only weak or isolated crossings.

### References:

- Radon, J. (1917). Über die Bestimmung von Funktionen durch ihre Integralwerte längs gewisser Mannigfaltigkeiten. *Berichte der Sächsischen Akademie der Wissenschaften zu Leipzig*, 69, 262–277.
- Hough, P. V. C. (1962). Method and Means for Recognizing Complex Patterns. U.S. Patent 3,069,654.
- Duda, R. O., and Hart, P. E. (1972). Use of the Hough Transformation to Detect Lines and Curves in Pictures. *Commun. ACM* 15(1), 11–15.
- van Ginkel, M., Luengo Hendriks, C. L., and van Vliet, L. J. (2004). A short introduction to the Radon and Hough transforms and how they relate to each other. *TU Delft Technical Report QI-2004-01*.

